

Title:

Resurface-Don't Replace-Your Worn Driveway

Word Count:

318

Summary:

Homeowners can easily repair and strengthen their driveways with a concrete resurfacer.

Keywords:

Resurface-Don't Replace-Your Worn Driveway

Article Body:

Your driveway is your home's first impression to the neighborhood. As the trend of remodeling

Resurface With A Squeegee

• With a simple squeegee application, the Quikrete Concrete Resurfacer provides a durable

How To Do It

• Begin by cleaning the driveway. This will ensure the concrete resurfacer properly bonds

• Follow the directions on the bag by blending the resurfacing mix with water until a po

• Use a pressure washer to clean the surface and saturate the driveway. Finish step by r

• Pour the mixture onto the concrete surface and then carefully spread with a long-handl

• Use the squeegee to scrub the material into the surface.

• For a slip-resistant professional finish, follow within 5 minutes with a broom making

• Wait 6 hours before allowing foot traffic and 24 hours for automobile traffic (with co

• Protect from rain for at least 6 hours, longer in cool or damp weather.

• Do not cover unless immediate rain protection is necessary. No sealer is required.

*If interested in a decorative finish, add desired Quikrete Cement Color to product mixture.

For thicker applications, use additional thin layers of the concrete resurfacer or use a trowel

This is a demo version of txt2pdf v.10.1

Developed by SANFACE Software <http://www.sanface.com/>

Available at <http://www.sanface.com/txt2pdf.html>